

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: UP0741V ACID #8 AEROSOL MIR COMPLIANT

Product code: ACIDV/AL

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: 1K ETCH PRIMER PAINT PRODUCT CONTAINING MIXTURE OF SOLVENTS

1.3. Details of the supplier of the safety data sheet

Company name: U-POL US Inc.
630 Selvaggio Drive
Suite 300
Nazareth
PA 18064
USA

Tel: 1-800-340-7824

Fax: 1-800-787-5150

Email: technical:u-pol.com

1.4. Emergency telephone number

Emergency tel: 1-800-424-9300 (CHEMTREC)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: F+: R12; Xi: R36; -: R66; -: R67

Most important adverse effects: Extremely flammable. Irritating to eyes. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

Classification under CLP: This product has no classification under CLP.

2.2. Label elements

Label elements under CHIP:

Hazard symbols: Extremely flammable.
Irritant.



Risk phrases: R12: Extremely flammable.
R36: Irritating to eyes.

SAFETY DATA SHEET

UP0741V ACID #8 AEROSOL MIR COMPLIANT

Page: 2

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Safety phrases: S2: Keep out of the reach of children.

S16: Keep away from sources of ignition - No smoking.

S23: Do not breathe vapour/spray

S38: In case of insufficient ventilation, wear suitable respiratory equipment.

Precautionary phrases: Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This substance is not identified as a PBT substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

ETHYL METHYL KETONE

EINECS	CAS	CHIP Classification	CLP Classification	Percent
201-159-0	78-93-3	F: R11; Xi: R36; -: R66; -: R67	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	10-30%

DIMETHYL ETHER

204-065-8	115-10-6	F+: R12	Flam. Gas 1: H220; Press. Gas: H250	30-50%
-----------	----------	---------	-------------------------------------	--------

1-METHOXY-2-PROPANOL

203-539-1	107-98-2	-: R10; -: R67	Flam. Liq. 3: H226; STOT SE 3: H336	1-10%
-----------	----------	----------------	-------------------------------------	-------

BUTAN-1-OL

200-751-6	71-36-3	-: R10; Xn: R22; Xi: R37/38; Xi: R41; -: R67	Flam. Liq. 3: H226; Acute Tox. 4: H302; STOT SE 3: H335; Skin Irrit. 2: H315; Eye Dam. 1: H318; STOT SE 3: H336	1-10%
-----------	---------	--	---	-------

XYLENE

215-535-7	1330-20-7	-: R10; Xn: R20/21; Xi: R38	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315	<1%
-----------	-----------	-----------------------------	---	-----

TERT-BUTYL ACETATE

208-760-7	540-88-5	F: R11; -: R66	Flam. Liq. 2: H225; -: EUH066	10-30%
-----------	----------	----------------	-------------------------------	--------

[cont...]

SAFETY DATA SHEET

UP0741V ACID #8 AEROSOL MIR COMPLIANT

Page: 3

ISOBUTANOL

201-148-0	78-83-1	-: R10; Xi: R37/38; Xi: R41; -: R67	Flam. Liq. 3: H226; Acute Tox. 4: H302; STOT SE 3: H335; Skin Irrit. 2: H315; Eye Dam. 1: H318; STOT SE 3: H336	<1%
-----------	---------	-------------------------------------	---	-----

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the

[cont...]

SAFETY DATA SHEET

UP0741V ACID #8 AEROSOL MIR COMPLIANT

Page: 4

contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	100 ppm	150 ppm	1 mg/m ³	-

Hazardous ingredients:

ETHYL METHYL KETONE

[cont...]

SAFETY DATA SHEET

UP0741V ACID #8 AEROSOL MIR COMPLIANT

Page: 5

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	600 mg/m ³	899 mg/m ³	-	-

DIMETHYL ETHER

UK	766 mg/m ³	958 mg/m ³	-	-
----	-----------------------	-----------------------	---	---

1-METHOXY-2-PROPANOL

UK	375 mg/m ³	560 mg/m ³	-	-
----	-----------------------	-----------------------	---	---

BUTAN-1-OL

UK	-	154 mg/m ³	-	-
----	---	-----------------------	---	---

XYLENE

UK	220 mg/m ³	441 mg/m ³	-	-
----	-----------------------	-----------------------	---	---

TERT-BUTYL ACETATE

UK	966 mg/m ³	1210 mg/m ³	-	-
----	-----------------------	------------------------	---	---

ISOBUTANOL

UK	154 mg/m ³	231 mg/m ³	-	-
----	-----------------------	-----------------------	---	---

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

Respiratory protection: Gas/vapour filter, type A: organic vapours (EN141).

Hand protection: Nitrile gloves.

Eye protection: Safety goggles. Ensure eye bath is to hand.

Skin protection: Protective clothing with elasticated cuffs and closed neck.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Aerosol

Colour: Pale grey

Odour: Characteristic odour

Evaporation rate: Moderate

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Insoluble

Also soluble in: Most organic solvents.

Flash point°C: -40

Relative density: 0.75

VOC g/l: 709 (5.95 lb/gal)

9.2. Other information

Other information: Not applicable.

[cont...]

SAFETY DATA SHEET

UP0741V ACID #8 AEROSOL MIR COMPLIANT

Page: 6

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

Section 11: Toxicological information

11.1. Information on toxicological effects

Relevant effects for mixture:

Effect	Route	Basis
Irritation	OPT	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: Not applicable.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

[cont...]

SAFETY DATA SHEET

UP0741V ACID #8 AEROSOL MIR COMPLIANT

Page: 7

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This substance is not identified as a PBT substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Deposit into or on to land (e.g. landfill, etc.)

Recovery operations: Use principally as a fuel or other means to generate energy.

Disposal of packaging: Dispose of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1950

14.2. UN proper shipping name

Shipping name: AEROSOLS

14.3. Transport hazard class(es)

Transport class: 2

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

[cont...]

SAFETY DATA SHEET

UP0741V ACID #8 AEROSOL MIR COMPLIANT

Page: 8

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

FOR PROFESSIONAL USE ONLY. Read full instructions before use.

IMPORTANT: This product contains hazardous materials and therefore appropriate personal protective equipment should always be used.

Please refer to the label and consult the material safety data sheet for full handling instructions and personal protection information. These are available via your local stockist or via the U-POL website at WWW.U-POL.COM.

U-POL disclaim any liability where the user does not wear the recommended personal protective equipment.

Phrases used in s.2 and 3: EUH066: Repeated exposure may cause skin dryness or cracking.

H220: Extremely flammable gas.

H225: Highly flammable liquid and vapour.

H226: Flammable liquid and vapour.

H302: Harmful if swallowed.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

R10: Flammable.

R11: Highly flammable.

R12: Extremely flammable.

R20/21: Harmful by inhalation and in contact with skin.

R22: Harmful if swallowed.

R36: Irritating to eyes.

R37/38: Irritating to respiratory system and skin.

R38: Irritating to skin.

R41: Risk of serious damage to eyes.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

[cont...]

SAFETY DATA SHEET

UP0741V ACID #8 AEROSOL MIR COMPLIANT

Page: 9

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. Addition of reducers, hardeners and other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, this company shall not be held liable for any damage resulting from handling or from contact with the above product.